

CHASSIS CONSTRUCTION FOR AN ARTICLE OF FOOTWEAR

Technical Field

The invention relates to the construction of a structural chassis for an article of footwear, such as a football shoe or a soccer shoe. The chassis is constructed to provide, in a pre-selected manner, comfort, flexibility, support, and power transfer by varying the configuration, thickness, and/or material of the chassis in various portions of the chassis, thereby tailoring flexibility and stiffness in the article of footwear.

Background Information

In sports such as football and soccer, speed and maneuverability are desirable skills. Properly designed athletic footwear can assist a player in enhancing those skills. The article of footwear should provide support to areas of the foot that need support, comfort to areas of the foot that need cushioning, flexibility to areas of the foot that need flexibility, and effective power transfer to areas of the foot where such power transfer will provide the most benefit to the wearer.

Conventional shoes manufactured for football and soccer have a stiff plastic outsole upon which studs, or cleats, are either integrally formed or attached. One method whereby desirable properties are optimized in one shoe is to manufacture an outsole with varying thickness and/or hardness (i.e., durometer), thus providing a shoe that provides comfort, support, flexibility, and power transfer to the parts of the shoe that most benefit from these properties; however, manufacturing a traditional molded outsole with variable thickness and hardness is difficult and expensive.

Summary of the Invention

An athletic shoe that provides comfort, support, flexibility, and effective power transfer can greatly enhance a player's performance. The invention relates to a chassis constructed to provide the desirable properties of comfort, support, flexibility, and effective power transfer without the difficulty and expense of trying to provide these properties in a traditionally molded outsole.

The flexibility offered by a shoe according to one embodiment of the present invention can be enhanced by replacing the hard plastic outsole of a traditional football or soccer shoe with a soft outsole and supplying the stiffness that is required with the hard chassis of the present invention. Additionally or alternatively, the hard plastic outsole of a traditional football or soccer shoe can be replaced with an integrally formed chassis and skin construct according to another embodiment of the present invention.

In one aspect of the invention, the chassis includes three sections or portions. A first section of the chassis is a midfoot portion. Extending generally from the midfoot portion into a toe portion is a forefoot portion. The forefoot portion includes at least one finger-shaped element. Extending generally from the midfoot into a heel portion is a rearfoot portion. The rearfoot portion also includes at least one finger-shaped element.

In one embodiment, one or more finger-shaped elements of the forefoot can extend along the entire length of the forefoot region of the footwear. In another embodiment, one or more finger-shaped elements of the rearfoot can extend along the entire length of the rearfoot region of the footwear. In other embodiments, the forefoot portion, rearfoot portion, or both can include three finger-shaped elements. The finger-shaped elements can be disposed adjacent to one another forming spaces or slits therebetween. In still other embodiments, the finger-shaped elements of the forefoot can be formed to include fold lines across a width of the forefoot portion. The midfoot portion of the chassis may also be a common midfoot portion. The finger-shaped elements of the forefoot portion of the chassis and any spaces therebetween may also span substantially the entire width of the forefoot region.

Additionally or alternatively, the rearfoot portion can be a single element defining an opening. The opening can be located in a heel region of the rearfoot portion. The opening can be of any shape including, but not limited to, a circle, an oval, a square, a triangle, a rectangle, or a diamond. In another embodiment, the rearfoot portion comprises two elements defining an opening therebetween. The opening may be in the form of a chevron. The chevron may open to either a lateral side or a medial side of the article of footwear.

In another aspect of the invention, the chassis can include a plurality of elements extending generally from a heel portion to a toe portion including a midfoot portion, a forefoot portion, and a rearfoot portion. In one embodiment, the elements can extend substantially along an entire length of an article of footwear. The elements can be adjacent to each other and/or spaced apart, as a function of longitudinal location. In embodiments having spaces, the spaces between the elements may be smaller than an inch, half an inch, or a quarter of an inch. In some embodiments, the elements and any spaces therebetween can span substantially the entire width of the sole.

A further aspect of the invention includes an article of footwear having a sole adapted to accommodate a chassis. In a further embodiment of the invention, an article of footwear includes a sole having a chassis integrally formed with a skin. The chassis can be integrally formed with a skin by processes such as dual injection and reverse injection. Dual injection is the process whereby two or more different materials (injectants) are injected simultaneously into a mold. Reverse injection is the process whereby a first injectant is used to create a mold (or mantel) for the second injectant (or inlays). This is the opposite of the general procedure where the first injectant is injected around the inlays (second injectant). The processes can include a single injection point or multiple injection points. In one embodiment, the chassis/skin construct includes a midfoot portion, a forefoot portion, and a rearfoot portion. In another embodiment, the midfoot portion can be a common midfoot portion. The forefoot portion and the rearfoot portion extend in opposite directions from the midfoot portion toward the toe portion and the heel portion, respectively. The forefoot portion, rearfoot portion, or both the forefoot portion and rearfoot portion can include at least one finger-shaped element. In another embodiment, the chassis/skin construct can include a plurality of elements, each element having a midfoot portion,

a rearfoot portion, and a forefoot portion. The elements can extend substantially along an entire length of the article of footwear. The elements can be adjacent to one another and may form spaces therebetween.

In some embodiments, an intermediate layer of material of a liquid or a solid can be disposed optionally between the integrally formed chassis and skin. In one embodiment, the layer of material can be a film. It is desirable that the film be chemically compatible with the chassis and the skin to maintain the integrity of the integrally formed chassis/skin construct. The film may contain graphics printed on the film with inks to enhance the visual appeal of the footwear when used with a transparent skin. The chassis/skin construct can be used as an outsole of an article of footwear.

In another aspect of the invention, the chassis or chassis/skin construct can include at least one lug or root extending from a bottom side of the chassis. The lug can extend into an integrally formed or attached cleat or spike element. The shape of the lug can mimic the shape of the cleat within which the lug extends.

In another aspect of the invention, the thickness of the chassis or chassis/skin construct can be varied. In one embodiment, the thickness of a first portion of the chassis or chassis/skin construct is different from the thickness of a second portion. For example, the first portion and the second portion can be the forefoot and the rearfoot portions, the midfoot and forefoot portions, or the midfoot and rearfoot portions. The first and second portions can also be the individual finger-shaped elements of the forefoot and/or rearfoot portions. In another embodiment, the chassis or chassis/skin construct includes more than two portions, each portion having a different thickness.

In another aspect of the invention, the chassis or chassis/skin construct can be made from two or more materials with differing properties. In one embodiment, the chassis or chassis/skin construct includes a first portion made from a material with properties different from a material of a second portion of the chassis or chassis/skin construct. In another embodiment, the chassis or chassis/skin construct includes more than two portions, each portion being made from materials with differing properties.

These and other objects, along with advantages and features of the present invention herein disclosed, will become apparent to those skilled in the art through reference to the following description of various embodiments of the invention, the accompanying drawings, and the claims.

Brief Description Of The Drawings

In the drawings, like reference characters refer to the same parts throughout the different views. Also, the drawings are not necessarily to scale, emphasis instead generally being placed upon illustrating the principles of the invention.

Figs. 1A-1G are schematic plan and cross-sectional views of one embodiment of the chassis of the present invention.

Figs. 2A-2G are schematic plan and cross-sectional views of another embodiment of the chassis of the present invention.

Figs. 3A-3I are schematic plan, side, cross-sectional, and end views of one embodiment of the chassis/skin construct of the present invention.

Fig. 4 is a schematic plan view of another embodiment of a chassis of the present invention.

Description

Embodiments of the present invention are described below. It is, however, expressly noted that the present invention is not limited to these embodiments, but rather the intention is that all equivalents and modifications that are obvious to a person skilled in the art are also included. In particular, the present invention is not intended to be limited to football and soccer shoes, but rather may be used for all types of footwear where comfort, support, flexibility, and effective power transfer are sought.

According to one embodiment of the present invention, an article of footwear includes a chassis that is disposed beneath the foot of the wearer. This can be achieved by integrating the chassis into an outsole of the article of footwear, or sandwiching it between the outsole and a

midsole, or between the midsole and an insole. The different possible arrangements of the chassis within the footwear may influence the functional properties of the article of footwear including the chassis; therefore, reference is made to an article of footwear in general.

Figs. 1A-1G depicts one embodiment of a chassis 2 of the present invention. Fig. 1A shows a plan view of the bottom of the chassis 2. The chassis 2 includes a common midfoot portion 4, a forefoot portion 6, and a rearfoot portion 8. Lines of demarcation between these portions are not fixed and may vary as a function of chassis design. The forefoot portion 6 and the rearfoot portion 8 extend from the midfoot portion 4 in opposite directions to a toe portion 7 and a heel portion 9, respectively. The forefoot portion 6 can include one or more finger-shaped elements 10, such as the three depicted in this embodiment. The finger-shaped elements 10 can be adjacent one another and may form spaces 14 therebetween. The spaces 14 between the finger-shaped elements 10 can extend from the midfoot portion 4 to the end of the forefoot portion 6. The spaces 14 need not be of uniform width and need not be partially or wholly linear.

The rearfoot portion 8 can include a single element 20 defining an opening 12. The opening 12 of the rearfoot portion 8 can be any shape. For example, the shape of the opening 12 can include, but is not limited to, a triangle, a circle, a square, a rectangle, or a chevron. Alternatively or additionally, the single element 20 of the rearfoot portion 8 can define more than one opening 12 and can open out to the medial side or the lateral side of the rearfoot portion 8.

Referring still to Fig. 1A, the chassis 2 may be designed to provide support to those areas of the article of footwear where a user would most benefit from having such support. For example, the chassis 2 has stiff finger-shaped elements 10 that are positioned above a row of cleats affixed to the outsole as shown in the embodiment depicted in Figs. 2A-2G. This improves the distribution of pressure caused by the lugs and cleats and enhances a wearer's comfort of the finished article of footwear. Also, a shank area 16 of the footwear typically requires strong support. Therefore, the chassis 2 can be designed to cover the entire midfoot portion 4 without openings or slits. The stiff chassis 2 also provides the necessary support needed when a soft outsole, such as one made of soft thermoplastic polyurethane or equivalent materials, is used instead of a traditional hard sole.

Areas of the footwear that require more flexibility typically require a less stiff chassis 2, allowing those areas to be more compliant to pressure. The design of the chassis 2, as well as the selection of material, can provide even greater flexibility. For example, certain areas of the forefoot portion 6, such as the finger-shaped elements 10 and the spaces 14 in the forefoot portion, form a forefoot flex zone 18. The forefoot flex zone 18 allows for greater maneuverability, especially when a wearer, such as a football player, needs to change directions quickly. Therefore, even with stiff finger-shaped elements 10 of the forefoot portion 6 for providing effective power transfer for toe off, the flexibility of the footwear can be improved by the use of a soft outsole, instead of the traditional hard outsole. A soft outsole allows for greater flexibility because the wearer can use the spaces 14 between the finger-shaped elements 10 to take advantage of the soft, flexible, and compressible outsole, instead of being limited in movement by the traditional hard, relatively inflexible outsole.

An additional advantage provided by the finger-shaped elements 10 and spaces 14 therebetween over the conventional stiff plates or inflexible outsoles is that the chassis 2 of the present invention allows the wearer to better “feel” the position of his foot relative to the ground. The design of the finger-shaped elements 10 allows the elements 10 to contort somewhat independently from each other in response to the position of the foot relative to the ground or the forces that are being applied to different areas of the foot. In contrast, the conventional stiff plate or inflexible outsoles tends to homogenize or mute the sensory input felt by the foot in response to the forces applied and the position of the foot relative to the ground.

The chassis 2 of the present invention allows a user to be in better communication with his environment. When a user’s ability to feel his foot working as he maneuvers over the ground is enhanced, it can increase his perception of his body in relation to his surroundings and increase his confidence in the consequences of his actions. One benefit is that he will be able to commit more of his energies to a given movement more quickly, without fear of a misstep or injury.

Figs. 1B-1D show a schematic cross-sectional view along section 1B-1B, a lateral side view, and a medial side view of the chassis 2, respectively. The forefoot portion 6 extends generally from the midfoot portion 4 into the toe portion 7. The rearfoot portion 8 extends generally into the heel portion 9. The opening 12 is defined by the singular finger-shaped

element 20 of the rearfoot portion 8. The chassis 2 is generally planar; however, the chassis 2 may be contoured to better conform to the shape of a foot. For example, Figs. 1B-1D show the chassis 2 offset in an arch region 17 to support a wearer's arch. The chassis 2 may also have a three-dimensional shape. Examples of three-dimensional elements are side elements 128 and
5 lugs or roots 130, described further in Figs. 2A-2G.

Figs. 1E-1G show schematic views of cross-sections 1E-1E, 1F-1F, and 1G-1G of the chassis 2 of Fig. 1A, respectively. Between the finger-shaped elements 10 of the forefoot portion 6 are spaces 14 to allow for greater flexibility. The midfoot portion 4 includes the shank area 16. The rearfoot portion 8 includes the finger-shaped element 20 defining an opening 12.

2009' 91' ~~Fig. 2A depicts a bottom plan view of another embodiment of the chassis 102 of the present invention. In this embodiment of the chassis 102, the finger-shaped elements 110 in the forefoot portion 106 have fold lines 122 as well as spaces 114 therebetween. The fold lines 122 and spaces 114 of the finger-shaped elements allow for greater flexibility in the forefoot region 106. In the process of walking or running, the forefoot region 106 of a wearer bends as he shifts his weight from his heel to his forefoot and then pushes off with the forefoot. These finger-shaped elements 110 and spaces therebetween 114 allow for greater and easier bending in this region.~~

The chassis 102, as shown in Figs. 2A-2G, can also include lugs or roots 130. The lugs 130 extend from the bottom side of the chassis 102 and generally mimic the shape of a cleat, filling an interior portion thereof. The lugs 130 and chassis 102 can form a system to provide enhanced comfort, flexibility, and power transfer. A lug 130 can extend from the bottom side of the chassis 102 into the cleat. The chassis 102 and lugs 130 work together to create a system to provide greater comfort to the wearer and greater power to his movements.

Lugs 130 extend from the bottom side of the chassis into the cleat of an article of footwear. The weight of the wearer, and any additional forces that are applied to his feet when a wearer moves, can be felt in that area of the foot above the cleats. This pressure is known as the point load, and it can produce an unpleasant ache in that local area of the foot. In the present embodiment, pressure exerted by the cleats are transferred to the lugs 130 which then allow the

pressure to be dispersed to a larger area, i.e., throughout the chassis, thus eliminating the uncomfortable point load. Thus, the wearer would never feel the pressure exerted by any individual lug 130 even if he were to apply all his weight and force to only one lug 130.

Moreover, the flexibility afforded by the finger-shaped elements 110 also lends itself to more powerful movements and control of the movements. The interconnected lugs 130 and the flexibility of the chassis 102 allow more cleats to be in contact with the ground, allowing the wearer to have more control over his movements (e.g., stop, go, and turn) and produce more forceful movements. This flexibility also lends itself to an increased ability of the user to "feel" the ground, as discussed previously. As a lug 130 is placed on the ground, that lug 130 tends to pull the other interconnected lugs 130 along a finger-shaped element 110 also to the ground. This system allows more cleats along a longitudinal length of the forefoot region 106 to be in contact with the ground. In addition, the spaces 114 between the finger-shaped elements 110 allow the finger-shaped elements 110 to bend longitudinally along the length of the finger-shaped elements 110, as well as allowing for some torsional rotation of each finger-shaped element 110. This flexibility allows more cleats along a lateral width to be in contact with the ground. For example, with a traditional chassis or hard outsole, a runner making a sharp left-handed turn will have only his cleats on the medial side of his outside running foot pushing off the ground. The flexibility of the chassis 102 of the present invention may allow the central as well as the lateral cleats to be in contact with the ground during push off. Thus, it would be a rare situation where all the weight of a wearer and/or the force of his movements would be borne on only one lug 130.

As well as providing for more flexibility and comfort, the chassis 102 may also provide for greater power transfer. The material of the chassis 102 may be one with good shape memory characteristics. A material that has a good memory is one that quickly and/or easily returns to its original shape after the force loads are removed from the elastically deformed material. A chassis 102 made of such a material allows the energy expended by the wearer to deform the chassis 102 and, when he rolls to the balls of his feet, to return the energy to the wearer when the deformed chassis 102 returns to its original shape. The better the memory of a material of the chassis 102, the greater the energy returned to the wearer.

The opening 112 in the heel portion 108, in this embodiment, is in the shape of a chevron. Similar to the triangular opening 12 shown in Fig. 1A, the chevron shaped opening 112 allows for comfort as it provides cushioning in the heel region 109; however, this shape can also accommodate the cleat formation in the heel region 209 as shown in Fig. 3A. The chevron opens to the lateral side 126 of the chassis 102 for added comfort in the heel region 109, allowing more cushioning; however, it is contemplated that the chevron may open to the medial side 124 of the chassis 102.

The chassis 102 can be three-dimensional. For example, the chassis 102 may include side elements 128 extending outward and upward from the midsole 104 on the medial side 124 of the chassis 102 and the lateral side 126 side of the chassis 102. One advantage of side elements 128 is that the design of the side element can be adjusted to provide more or less support in the shank region 116. Support in the shank region 116 can be tunable by adjusting the side elements 128, the durometer of a material, and/or the thickness of the material.

Figs. 2B-2D show a cross-sectional view along section 2B-2B, a lateral side view, and a medial side view of Fig. 2A. Figs. 2E-2G show cross-sectional views along sections 2E-2E, 2F-2F, and 2G-2G of Fig. 2A.

~~In Fig. 2, Figs. 3A-3I depict still another embodiment of the chassis 202 of the present invention. In this embodiment, the chassis 202 is integrally formed with a skin 238. Cleats 234 extend from a bottom side of the chassis/skin construct 201. Lugs 230 extend from the bottom side of the chassis 202 into some of the cleats 232. Other cleats 234 may not have lugs. As described above, the lugs 230 and chassis 202 form a system for improved comfort, greater maneuverability, and more powerful movements.~~

~~In Fig. 3, Fig. 3A shows a plan view of the bottom side of the chassis/skin 201. The finger-shaped elements 210 in the forefoot region 206 have fold lines 222 to facilitate flexing at these regions. The opening 212 in the heel portion 209 is in the shape of a chevron. Figs. 3B-3C show a cross-sectional view along section 3B-3B, a medial side view, and a lateral side view, respectively, of the chassis/skin construct 201. Figs. 3E-3G show cross-sectional views along sections 3E-3E,~~

3F-3F, and 3G-3G of the chassis/skin construct 201. Figs. 3H-3I show end views of a toe view and a heel view, respectively.

The chassis 2, 102, 202 can be composed of any suitable polymeric material or combination of polymeric materials, either with or without reinforcement. Suitable materials may include: thermoplastic polyurethane (TPU); thermoplastic polyether block amides, such as the Pebax[®] brand sold by Elf Atochem; thermoplastic polyester elastomers, such as the Hytrel[®] brand sold by DuPont; nylon 12, which may include 10 to 30 percent or more glass fiber reinforcement; and equivalent materials. Reinforcement, if used, may be by inclusion of glass or carbon graphite fibers or para-aramid fibers, such as the Kevlar[®] brand sold by DuPont, or other similar method. Other suitable materials will be apparent to those skilled in the art.

The material of the chassis 2, 102, 202 may advantageously possess good memory. This quality is desirable since, as discussed previously, the better the memory, the greater the ability of the material, and hence the chassis 2, 102, 202, to transmit energy back to the wearer.

In chassis/skin constructs 201, the chassis 202 and skin 238 can be integrally formed by a process called reverse injection. The skin 238 itself forms the mold for the chassis 202. Such a process is more economical than conventional methods, because a separate chassis mold is not required. The chassis/skin 201 can also be formed in a single step called dual injection, where two or more materials are injected simultaneously to integrally create the chassis 202 and the skin 238. These processes can also include multiple points of injection for the material for the chassis 202 and skin 238. The presence of these multi-injection points allows the manufacturer to produce very thin, but supportive structures. This is in contrast to a process with a single point of injection where it is very difficult to create a thin structure, as thin areas of the mold will tend to impede the flow of the viscous injectant into the mold, resulting in incomplete filling, referred to by those of skill in the art as a short shot.

The material for the chassis 202 and skin 238 should be "compatible." Being compatible means that the chassis 202 and skin 238 should be able to chemically bond to each other after the process of integrally forming them. It is also desirable that the material for the chassis 202 and skin 238 have similar limit radii. A limit radius is known in the art as the curvature of a length of

material when pressure is applied to bend it, without destroying the integrity of the material.

Because the chassis/skin construct 201 must undergo numerous amounts of bending and twisting when in use, a chassis 202 with a limit radius that is sufficiently different from the limit radius of the skin 238 could potentially cause the chassis 202 and skin 238 to separate because one

5 material would have a greater resistance to bending than the other. In other words, the greater resistance of one material can cause the two materials to be in tension with each other and, thus, can potentially destroy the chemical bond between the chassis 202 and skin 238.

In 494 ~~It is also contemplated that an intermediate layer of a liquid or a solid material, such as a thin film, can be disposed between the chassis 202 and skin 238 and that all three components~~

10 (the chassis 202, intermediate layer, and skin 238) are compatible with each other to create an integrally formed chassis/skin 201 structure. The intermediate liquid or solid material may be any material that allows the chassis 202 and skin 238 to be compatible as defined herein. For example, the intermediate layer may be an ink, a powder, a fabric, or a film of a natural or synthetic material. In one embodiment, the film is created with a color and/or design and the skin 238 is made of a transparent material so that the color and/or design of the film can be
5 readily viewed through the skin 238 to enhance visual appeal.

The sole can be composed of any suitable polymeric material or combination of polymeric materials, such as the materials discussed above, or more specifically, ethylene vinyl acetate (EVA), Pebax 5533, Pebax 6333, Pebax 7033, thermoplastic polyurethane-ether, such as
20 TPU-ether 500, or thermoplastic polyurethane ester. If, however, the chassis/skin construct 201 is to be used as an outsole, it is desirable that the skin 238 offer excellent wear/abrasion resistance.

The chassis 2, 102, 202 or chassis/skin construct 201 can be designed to provide more stiffness in certain areas of the article of footwear and less stiffness in other areas. The stiffness
25 of the chassis 2 can be controlled by varying the thickness, hardness, and/or width of the chassis 2, 102, 202 or chassis/skin construct 201. The thicker, harder, or wider the material in a particular area of the chassis 2, 102, 202, or chassis/skin construct 201, the stiffer the chassis 2, 102, 202 or chassis/skin construct 201 will typically be in that area. Thus, the chassis 2, 102, 202

or chassis/skin construct 201 can be designed to provide greater stiffness in one area of the chassis 2, 102, 202 or chassis/skin construct 201 than another area.

~~FIG. 3 shows another embodiment of the chassis 2, 102, 202, or chassis/skin construct 201 can also be designed to provide more stiffness to certain areas of the article of footwear and less stiffness to other areas by~~

~~5 varying the types of material used to manufacture the chassis 2, 102, 202 or chassis/skin construct 201. Thus, stiffer materials can be placed in areas requiring greater support and power transfer and less stiff materials can be placed in areas requiring greater flexibility, such as a forefoot flex region.~~

~~FIG. 4 shows another embodiment of the chassis 302 of the present invention. The chassis 302 includes three elements. In this embodiment, each element 310 includes a forefoot portion 306, a midfoot portion 304, and a rearfoot portion 308. The elements 310 extend substantially the entire length of an article of footwear. The elements 310 lie adjacent to one another and may form spaces 314 therebetween, as depicted. In a preferred embodiment, the chassis 302 is designed to support and work with cleats. Thus, elements 310 are placed and spaced in the footwear to support a cleat extending directly or indirectly from the bottom of the element 310.~~

The sole can be manufactured with a suitable configured recess to house the chassis 2, 102, 302. Alternatively, a sole including the chassis 2, 102, 302 can be manufactured by inserting the chassis 2, 102, 302 into an injection mold that may be used to produce a sole, and then injecting a polymer or similar material into the mold. Other methods of manufacturing the sole are the processes for chassis/skin construct 201 discussed previously. The materials forming the chassis 2, 102, 202, 302 and skin 238 can be injected in the same processing step to create the chassis/skin construct 201. This dual injection process allows the manufacturer to vary the thickness and/or durometer of the material of the chassis 2, 102, 202, 302 and/or skin 238 according to a wearer's needs and/or to a particular sport. In a reverse injection process, the materials forming the skin 238 can be used as a mold for the chassis 2, 102, 202, 302. Both of the latter methods described are more economical than the conventional process. Multi-point injections of the chassis 2, 102, 202, 302 and skin 238 also permit areas of the chassis 2, 102, 202, 302 to be thin, while still maintaining the chassis's structural integrity. In other words, the

chassis can be very thin and still provide stiffness and support as needed. In an alternative method of manufacturing the claimed invention, the chassis 2, 102, 202, 302 and skin 238 can be sandwiched and/or bonded together by other means known in the art to form a single unit.

Having described preferred and exemplary embodiments of the invention, it will be
5 apparent to those of ordinary skill in the art that other embodiments incorporating the concepts disclosed herein can be used without departing from the spirit and scope of the invention. The described embodiments are to be considered in all respects only as illustrative and not restrictive. Therefore, it is intended that the scope of the present invention be only limited by the following claims.

10 What is claimed is:

11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
22